

Product Datasheet

www.1-light.eu

67410A/AN/W

20 Garden & Underwater>The LED Bollards Range Cone reflector



20W LED Bollard, IP65 for Garden illumination.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads	Dimensions
	160mm 1 1 1000mm -
Physical Specification	

Item Group	20 Garden & Underwater
Family	The LED Bollards Range Cone reflector
Order Code	67410A/AN/W
Colour	Anthracite
Material	Die Cast
Diffuser Material	PC
Shape	Circular

Height	1000mm
Diameter	160mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No



Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	20W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	40V
Power(Watts)	20W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Osram

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes



Power(Watts)	15-21W
Power Factor	0,9
Constant Current	Yes
500mA	30-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	55°C
Operating Temp	85°C
Housing Material	Plastic
Output Terminal	Connector
Brand	HEP
Protection	Short Circuit

Illumination Data

Colour Temperature	3000K
Lumen Output	1600lm
Light Efficiency	80lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Weight	6.100kg
Pcs/Carton	2
Barcode	5291889057482

HS Code

9405413990



Certification & Warranty	
Warranty	3 Years
Average Lifetime	5000hours
Weee Directive	Yes

switch to one light!



