

## 14 Plafo>LED Aluminium Panel Range

## 62140RE/W/C



40W, 120x30cm LED slim plafo light, IP40, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



### Downloads



### Dimensions



### Physical Specification

Item Group	14 Plafo
Family	LED Aluminium Panel Range
Order Code	62140RE/W/C
Colour	White
Material	Aluminium
Shape	Rectangular
Length	1200mm
Width	300mm
Height	40mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Gear

External-Included

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

40W

IP Rating

IP40

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

1000mA

Voltage

38V

Safety Class



Power(Watts)

38W

IP Rating

IP40

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Sanan

F Mark



Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz


Yes

60 Hz

Yes

Power(Watts)	28,5-38W
Power Factor	0,9
Constant Current	Yes
1000mA	30-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	40°C
Operating Temp	80°C
Housing Material	Plastic
Output Terminal	Cable
Fast Connector	Yes
Fast Connector Type	Other
Brand	AGT

#### Illumination Data

Colour Temperature	4000K
Lumen Output	3600lm
Light Efficiency	90lm/W
CRI	80
Illumination Diagram	

#### Packing Info

Box Length	133cm
Box Width	36cm
Box Height	8,5cm
Box Weight	3.625kg
Pcs/Carton	4
Barcode	5291889052166
HS Code	9405413990

Warranty

2 Years

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

