

13 Wall & Ceiling LED>The Roof tile Range Die cast

67512/AN/W



8W Wall light, IP65.

Complete with 200mA driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

| | |
|-------------------|------------------------------|
| Item Group | 13 Wall & Ceiling LED |
| Family | The Roof tile Range Die cast |
| Order Code | 67512/AN/W |
| Colour | Anthracite |
| Material | ABS |
| Diffuser Material | PC |
| Shape | Rectangular |
| Length | 110mm |
| Width | 50mm |
| Height | 220mm |
| Surface Wall | Yes |
| Indoor | Yes |

Outdoor

Yes

Adjustable

No

Electrical Characteristics

Gear

Built In

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

8W

IP Rating

IP65

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

200mA

Voltage

33,5V

Power(Watts)

6,7W

IP Rating

IP65

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Epistar

Gear

Gear Type


Led Driver

Input Voltage


220-240V

50 Hz

Yes

| | |
|------------------|---|
| 60 Hz | Yes |
| Power(Watts) | 5,6-8,4W |
| Power Factor | 0,9 |
| Constant Current | Yes |
| 200mA | 28-42V |
| IP Rating | IP20 |
| Safety Class |  |
| Dimmable | No |
| Housing Material | Plastic |
| Brand | Eaglerise |
| Protection | 0 |

Illumination Data

| | |
|----------------------|---|
| Colour Temperature | 3000K |
| Lumen Output | 400lm |
| Light Efficiency | 50lm/W |
| CRI | 80 |
| Illumination Diagram |  |

Packing Info

| | |
|------------|---------------|
| Box Length | 23cm |
| Box Width | 12,5cm |
| Box Height | 6cm |
| Box Weight | 0.490kg |
| Pcs/Carton | 20 |
| Barcode | 5291889068921 |
| HS Code | 9405114090 |

Warranty

2 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

